

新产品



手机直连打印

iLabelPrint+
手机软件
制作标签

全新升级蓝牙桌面打印机

CP-3140EX Pro (B)



打印速度升级

打印速度高达4ips，高效提升生产力！



智能化升级

蓝牙连接打印，随时随地方便、快捷办公！



软件升级

自主研发APP (iLabelPrint+)，支持安卓系统与ios系统，方便快捷！



结构升级

同时可拥有小卷心与大卷心轴，随心替换不同卷心尺寸的碳带！

应用领域



商场零售



制造业



仓储物流



服装行业



规格		CP-3140EX Pro (B)	
列印方式	热敏式 & 热转式		
解析度	300 dpi (12 dots/mm)		
最大列印速度	4 ips		
最大列印长度	50" (1270 mm)		
最大列印宽度	4.16" (105.7 mm)		
记忆体	128MB SDRAM, 128MB Flash ROM		
中央处理器	32 位元 RISC 微处理器		
耗材规格			
感测装置	纸张反射式感测器(可调整)/纸张穿透式感测器(固定·居中)		
纸张种类	纸卷式、标籤式(间距纸、连续纸、折叠纸、票券、吊牌...等)		
纸张规格	最大宽度：4.65"(118mm) 最小宽度：0.8"(20mm) 纸张厚度：0.0024"~0.008"(0.06mm~0.2mm) 纸捲轴心0.5"(12.7mm)可容纸捲外径4.5"(114.3mm) 纸捲轴心1"(25.4mm)可容纸捲外径5"(127mm) 纸捲轴心1.5"(38.1mm)可容纸捲外径4.7"(120mm)		
碳带规格	宽度：1"~4.33"(25.4mm~110mm) 最大长度：300m 轴心内径：1"(25.4mm)或选配：0.5"(12.7mm)·轴心宽度：2.6"(67mm) 适用种类：蜡基、混合基、树脂基碳带(内/外碳带皆适宜)		
字型与条码			
字型	五种国际标准字型(1.25mm~6mm) 最大可达 24x24 四方向旋转0° ~ 270° 内建GB18030简中字体 可下载Windows True Type Font仿真字形		
一维条码	PPLA: Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random weight, Telepen, FIM, Interleaved 2 of 5 (Standard/with modulo 10 checksum / with human readable check digit/ with modulo 10 checksum & shipping bearer bars), and GS1 Data bar (RSS) PPLB: Code 39, UPC-A, UPC-E, Matrix 2 of 5, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2 /5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code) , Code 128 auto, UCC/EAN code 128 (GS1-128), Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5, EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, and GS1 Data bar (RSS) PPLZ: Code39, UPC-A, UPC-E, Postnet, Code128 subset A/B/C, Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, Code 93, Code 39 with check sum digit, MSI, EAN-8, Codabar, Code 11, EAN-13, Plessey, GS1 Data bar (RSS), Industrial 2 of 5, Standard 2 of 5, and Logmars		
二维条码	PPLA: PCX, BMP, IMG, HEX and GDI format files PPLB: PCX, PCX , BMP , Binary Raster, and GDI PPLZ: GRF, Hex and GDI		
图片格式	PPLA: PCX, BMP, IMG, HEX and GDI format files PPLB: PCX, BMP, Binary Raster, and GDI PPLZ: GRF, Hex and GDI		
指令集	PPLA, PPLB, PPLZ,Auto		
介面与配件			
配件	全切半切闸刀·旋刀·剥纸器·外置纸架		
操作介面	LED指示灯 x 2 · 按键 x 1		
通讯接口	USB接口 · 蓝芽v4.2		
驱动程式	Windows Driver for Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver		
工具软体	iLabelPrint, ArgoBar Pro, BarTender, Printer Tool, Font Utility, Command Library, Argox SDK		
数据库连结	提供ArgoBar Pro支持ODBC数据库连结：Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (*.dbf)		
电源与环境			
电源供应	切换式电源供应器 · 交流输入100~240V · 50~60Hz 直流输出 24V, 2.5A		
环境条件	操作环境：40°F~100°F (4°C~38°C). 相对溼度：10%~90% 储存环境：-4°F~122°F (-20°C~50°C).		
安规认证	CE, FCC, cULus, CCC, RoHS, BIS, BSMI, KC		
物理规格			
尺寸	宽 226mm x 高 188mm x 深 276mm		
重量	4.6 lbs (2.1 kg)		

*本规格未来如有变更·请依实际出厂为主·不再另行通知。



ARGOX Certified Repair Centers

请咨询当地的合作伙伴
以了解更多讯息

