

新产品

GT-820 Pro



最超值的 桌面打印机



手机直连打印



手机软件
制作标签

使用前



花费大量的时间和金钱，却只能用到前一代的低阶桌上型条码机。

使用后



使用新一代的桌上型条码机，有效节省时间和人力。

应用



商场零售



制造业




仓储物流



服装行业



功能丰富，使日常工作简单易行



Shell Suit 设计

通讯接口内缩能将所有重要的连接线收到条码印表机下方，除了节省桌面空间之外，也能保护排线接头。



安装纸卷更容易

加大空间，碳带和纸卷的安装更简单方便。



超长的使用寿命

继承乌龟精神，一体成型式的结构能够让GT-820 Pro印表机坚固又耐用。



效能更加提升

选配蓝牙，支持Argox iLabel Print手机版标签编辑App，及开发微信小程序打印标签。



规格		GT-820 Pro	
列印方式	热敏式 & 热转式		
解析度	203 dpi (8 dots/mm)		
最大列印速度	6 ips		
最大列印长度	100" (2540 mm)		
最大列印宽度	4.25" (108 mm)		
记忆体	128MB SDRAM, 128MB Flash ROM		
中央处理器	32 位元 RISC 微处理器		
耗材规格			
感测装置	纸张反射式感测器(可调整)/纸张穿透式感测器(固定·居中)		
纸张种类	纸卷式、标籤式(间距纸、连续纸、折叠纸、票券、吊牌...等)		
纸张规格	最大宽度：4.65"(118mm) 最小宽度：0.8"(20mm) 纸张厚度：0.0024"~0.008"(0.06mm~0.2mm) 纸捲轴心0.5"(12.7mm)可容纸捲外径4.5"(114.3mm) 纸捲轴心1"(25.4mm)可容纸捲外径5"(127mm) 纸捲轴心1.5"(38.1mm)可容纸捲外径4.7"(120mm)		
碳带规格	宽度：1"~4.33"(25.4mm~110mm) 最大长度：300m 轴心内径：1"(25.4mm)或选配：0.5"(12.7mm)·轴心宽度：2.6"(67mm) 适用种类：蜡基、混合基、树脂基碳带(内/外碳带皆适宜)		
字型与条码			
字型	五种国际标准字型(1.25mm~6mm)·最大可达 24x24 四方向旋转0°~270°·内建GB18030简中字体 可下载Windows True Type Font仿真字形		
一维条码	PPLA: Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random weight, Telepen, FIM, Interleaved 2 of 5 (Standard/with modulo 10 checksum / with human readable check digit/ with modulo 10 checksum & shipping bearer bars), and GS1 Data bar (RSS) PPLB: Code 39, UPC-A, UPC-E, Matrix 2 of 5, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2/5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code) , Code 128 auto, UCC/EAN code 128 (GS1-128), Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5, EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, and GS1 Data bar (RSS) PPLZ: Code39, UPC-A, UPC-E, Postnet, Code128 subset A/B/C, Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, Code 93, Code 39 with check sum digit, MSI, EAN-8, Codabar, Code 11, EAN-13, Plessey, GS1 Data bar (RSS), Industrial 2 of 5, Standard 2 of 5, and Logmars		
二维条码	PPLA: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, and Composite Codes PPLB: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, and Composite Codes PPLZ: QR code, PDF417, Data Matrix (ECC 200 only), and MaxiCode Composite Codes		
图片格式	PPLA: PCX, BMP, IMG, HEX and GDI format files PPLB: PCX, BMP, Binary Raster, and GDI PPLZ: GRF, Hex and GDI		
指令集	PPLA, PPLB, PPLZ		
介面与配件			
配件	全切半切闸刀·旋刀·剥纸器·外置纸架		
操作介面	LED指示灯 x 2·按键 x 1		
通讯接口	USB接口·蓝芽v4.2(选配)		
驱动程序	Windows Driver for Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver		
工具软体	ArgoBar Pro, BarTender, Printer Tool, Font Utility, Command Library, Argox SDK		
手机应用程序	iLabelPrint+		
数据库连结	提供ArgoBar Pro支持ODBC数据库连结：Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (*.dbf)		
电源与环境			
电源供应	切换式电源供应器·交流输入100~240V·50~60Hz 直流输出 24V, 2.5A		
环境条件	操作环境：40°F~100°F (4°C~38°C). 相对溼度：10%~90% 储存环境：-4°F~122°F (-20°C~50°C).		
安规认证	CCC, RoHS		
物理规格			
尺寸	宽 226mm x 高 188mm x 深 276mm		
重量	4.6 lbs (2.1 kg)		

*本规格未来如有变更·请依实际出厂为主·不再另行通知。

